

Digital Signage

Freestanding all-in-one kiosk



Cutting edge signage solution

Promotional focal point

Highly versatile

WiFi Data transfer

Touch Screen or Standard options available



NEW!
Digital
A-Frame

SIMPLE. SMART. VERSATILE.



ALLPRIDE
SIGNS Est.1989

Digital Signage

Freestanding all-in-one kiosk



Our innovative all-in-one touchscreen kiosks are designed to advertise, inform and entertain. **Simple, smart and versatile** our kiosks are an ideal choice for a wide range of applications in all areas of your club or pub.

PERFECT FOR:

- Interactive Menus
- Club promotions
- Split screen content
- Video advertisements
- Interactive Honour boards
- Event and function promotion

HOW IT WORKS



Upload desired content to linked computer

Content uploaded to kiosk via the Internet (wireless)

Content displayed on kiosk screen

Specification model

Panel size	32", 42", 46", 47", 50", 55"
Display area(mm)/mode	1018(L)*578(W) 4:3
Maximum resolution	1920*1080
Display color	16.7M
Pixel Pitch(mm)	0.264(H)*0.264(V)
Brightness (nits)	450cd
Contrast	4000
Visual angle	178°/178°
Response time	5ms
Horizontal frequency	50-70KHZ
Vertical frequency	56-75KHZ
Life(hrs)	>60,000(hrs)

Touch Panel

Specification	ir-frame 6 POINTS touches
"Positioning accuracy"	±1mm
Transmittance	≥95%
Hardness	7H
Click manner	4 points
Response time	≤10ms
Output Resolution	4096X4096
Glass	tempered glass 4 mm

Video

Color system	PAL/NTSC/SECAM
Compatible HDMI input/DVI	480P,576P,720P,1080i,1080P

Accessories

Manual, warranty card, power cable, etc.

Warranty

1 year Quality with life long online technician support

Computer

Menu language	English
Main chipset	H61
CPU	"Intel core i3-3470 3.2GHz"
Memory	4Gb
Hard Disk	SATA II 5400 500GB
Interface	VGA*1, USB*2, RJ45*1 HDMI
Storage	1G DDR3
Flash	8G SUPPORT 16G
CPU	A20 dual core 1.2 Ghz quad-core RK3188

Power

Power supply	AC100V~240V,50/60Hz
Maximum power consumption	≤220W
Standby power consumption	≤1W

Temperature

Working temperature	0°C~50°C
Storage temperature	-10°C~60°C
Working humidity	20%~80%
Storage humidity	5%~95%

Appearance

Body dimension(Lx W x H)mm	Customised
Panel color/appearance	White, black, Customised
Panel material	SPCC/Aluminum/Customised
Installation	Floor standing
Certificate	CE/FCC/3C/RoHS



ALLPRIDE SIGNS
Est.1989

(Ph) 02 4942 3099 (Fax) 02 4947 8444 (Email) sales@allpride.com.au
(Address) 1/18 Oakdale Rd, Gateshead NSW 2290

Digital Honour Boards



Bring your honour boards into the digital age with our all-in-one Interactive Honour Board display. **Simple, smart** and **versatile** this system is designed to simplify your honour board updating process.

KEY FEATURES:

- Streamlined updating process
- Endless design options
- Interactive display
- Highly versatile
- All-In-one package, freeing up wall space

HOW IT WORKS



Upload desired content to linked computer

Content uploaded to kiosk via the Internet (wireless)

Content displayed on kiosk screen

Specification model

Panel size	32", 42", 46", 47", 50", 55"
Display area(mm)/mode	1018(L)*578(W) 4:3
Maximum resolution	1920*1080
Display color	16.7M
Pixel Pitch(mm)	0.264(H)×0.264(V)
Brightness (nits)	450cd
Contrast	4000
Visual angle	178°/178°
Response time	5ms
Horizontal frequency	50-70KHZ
Vertical frequency	56-75KHZ
Life(hrs)	>60,000(hrs)

Touch Panel

Specification	ir-frame 4 POINTS touches
"Positioning accuracy"	±1mms
Transmittance	≥95%
Hardness	7H
Click manner	4 points
Response time	≤10ms
Output Resolution	4096X4096
Glass	tempered glass 4 mm

Video

Color system	PAL/NTSC/SECAM
Compatible HDMI input/DVI	480P,576P,720P,1080i,1080P

Accessories

Manual, warranty card, power cable, etc.

Warranty

1 year Quality with life long online technician support

Computer

Menu language	English
Main chipset	H61
CPU	"Intel core I3-3470 3.2GHz"
Memory	4Gb
Hard Disk	SATA II 5400 320GB
Interface	VGA*1, USB*2, RJ45*1 HDMI
Storage	1G DDR3
Flash	8G SUPPORT 16G
CPU	A20 dual core 1.2 Ghz quad-core RK3188

Power

Power supply	AC100V~240V,50/60Hz
Maximum power consumption	≤220W
Standby power consumption	≤1W

Temperature

Working temperature	0°C~50°C
Storage temperature	-10°C~60°C
Working humidity	20%~80%
Storage humidity	5%~95%

Appearance

Body dimension(Lx W x H)mm	Customised
Panel color/appearance	White, black, Customised
Panel material	SPCC/Aluminum/Customised
Installation	Floor standing
Certificate	CE/FCC/3C/RoHS



ALLPRIDE
SIGNS Est.1989

(Ph) 02 4942 3099 (Fax) 02 4947 8444 (Email) sales@allpride.com.au
(Address) 1/18 Oakdale Rd, Gateshead NSW 2290